



Preservation & Sealing Tape



Backing Carrier:	LDPE Film
Adhesive:	Rubber (R400)
Release Liner:	N/A
Standard Colors:	Clear
Standard Sizes:	Incremental widths 1/4" - 46" x 108ft

Applications

- Sealing, patching, and splicing polyethylene sheeting or shrink film used for construction, mobile homes, outdoor equipment, and material storage
- Used in suncatcher production to secure frames during epoxy painting, allowing for a clear, defect-free surface.
- General purpose patch and repair

Features

LDPE Film

Rubber Adhesive

Benefits

- Conformable for irregular surfaces
- Abrasion resistant
- Transparent for less visible repairs
- Moisture, solvent, and chemical resistant
- Good quick stick
- Sticks aggressively to most surfaces
- Smooth unwind

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesion to Steel	25 oz/in	2.74 N/cm	ASTM D-3330
Tensile Strength	15 lb/in	26.27 N/cm	ASTM D-3759
Elongation	450 %		
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	50 to 190 °F	10 to 88 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.