



Aircraft Preservation & Sealing Tape



- Backing Carrier:** UV Stabilized LDPE Film
- Adhesive:** Rubber
- Release Liner:** N/A
- Standard Colors:** White
- Standard Sizes:** Incremental widths 1/4" - 48" x 108ft

Applications

- Long-term preservation, sealing, and splicing
- Splicing, seaming, and sealing polyethylene films
- Direct protective mask and surface protection for aircraft
- Used in conjunction with outdoor shrink film to secure film and seal film edges for extended outdoor storage

Features

LDPE Film

Rubber Adhesive

Benefits

- Conformable for irregular surfaces
- Abrasion resistant
- UV and weather resistant
- Moisture, solvent, and chemical resistant
- Good quick stick
- Excellent adhesion to PE and shrink film
- Clean removal from most surface
- Resists staining and ghosting
- Excellent low-temperature adhesion

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesion to Steel	25 oz/in	2.74 N/cm	ASTM D-3330
Tensile Strength	17 lb/in	29.77 N/cm	ASTM D-3759
Elongation	600 %		
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	-40 to 200 °F	-40 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.