



PE Acid-Free Overlaminating Tape



- Backing Carrier:** LDPE Film
- Adhesive:** Acid-Free Acrylic (A115)
- Release Liner:** N/A
- Standard Colors:** Clear
- Standard Sizes:** Incremental widths 1/4" - 54" x 60ft

Applications

- Protective overlaminate for graphics, signs, and placards.
- Surface protection against moisture, UV, solvents, and abrasion

Features

LDPE Film

Acid-Free Acrylic Adhesive

Benefits

- Tough and abrasion resistant
- Conformable
- Stands up to harsh environments
- Super clear film for invisible protection
- Adheres aggressively to surfaces
- Non-yellowing
- No edge bleed
- Excellent long-term stability

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesion to Steel	70 oz/in	7.66 N/cm	ASTM D-3330
Tensile Strength	10 lb/in	17.51 N/cm	ASTM D-3759
Elongation	400 %		
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	-40 to 200 °F	-40 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.