



10 mil Contractor Grade Duct Tape

Backing Carrier: LDPE Film
Adhesive: Acrylic
Release Liner: N/A
Standard Colors: Clear, Transparent Orange
Standard Sizes: Incremental widths 1/4" - 54" x 108ft Perforated spacing available

Applications

- Tip tape for corner protection on automotive glass during transport and storage
- Designed and sold exclusively to Gold Glass Group

Features

Benefits

LDPE Film

- Thick and highly conformable
- Abrasion and moisture resistant
- Perforated spacing available

Acrylic Adhesive

- Solvent resistant
- Excellent high and low temperature performance
- Removes cleanly - will not leave residue
- Easy to apply

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesion to Steel	20 oz/in	2.19 N/cm	ASTM D-3330
Tensile Strength	12 lb/in	21.02 N/cm	ASTM D-3759
Elongation	550 %		
Application Temperature	32 to 120 °F	49 °C	
Operating Temperature	-40 to 190 °F	-40 to 88 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.