



Removable PE Auto-Glass Tape



- Backing Carrier:** LDPE Film
- Adhesive:** Acrylic (A200)
- Release Liner:** N/A
- Standard Colors:** Clear, Transparent Orange
- Standard Sizes:** Incremental widths 1/4" - 54" x 108ft Easy tear version also available

Applications

- Auto glass molding retention tape for use in windshield and auto glass replacement or installation
- Tip tape for corner protection on automotive glass during transport and storage

Features

LDPE Film

Acrylic Adhesive

Benefits

- Thick and highly conformable
- Abrasion and moisture resistant
- Perforated spacing available
- Solvent resistant
- Excellent high and low temperature performance
- Removes cleanly - will not leave residue
- Easy to apply

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesion to Steel	12 oz/in	1.31 N/cm	ASTM D-3330
Tensile Strength	12 lb/in	21.02 N/cm	ASTM D-3759
Elongation	500 %		
Application Temperature	32 to 120 °F	49 °C	
Operating Temperature	-40 to 190 °F	-40 to 88 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		