



Polyethylene-Removable Protective Film



- Backing Carrier:** LDPE Film
- Adhesive:** Acrylic
- Release Liner:** Self Wound or with 66# Clay Coated Kraft
- Standard Colors:** Clear, Transparent Orange, White
- Standard Sizes:** Incremental widths 1/4" - 54" x 108ft

Applications

- Surface and label overlaminates.
- Protective masking on plastics and metals during shipping and assembly - saves money by reducing damage to delicate surfaces!
- Temporary surface protection

Features

LDPE Film

Acrylic Adhesive

Benefits

- Thick and highly conformable
- Abrasion and moisture resistant
- Perforated spacing available
- Solvent resistant
- Excellent high and low temperature performance
- Removes cleanly - will not leave residue
- Easy to apply

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesion to Steel	12 oz/in	1.31 N/cm	ASTM D-3330
Tensile Strength	12 lb/in	21.02 N/cm	ASTM D-3759
Elongation	500 %		
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	-40 to 190 °F	-40 to 88 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.