



Removable Aircraft Surface Protection Tape



Backing Carrier: LDPE Film
Adhesive: Acrylic
Release Liner: N/A
Standard Colors: Clear, Transparent Orange
Specifications: FAR 25.853(a)
Note: Colors: Clear, Transparent Orange
Standard Sizes: Incremental widths 1/4" - 54" x 108ft

Applications

- Aircraft general surface protection applications on various interior materials during maintenance and repair operations.

Features	Benefits
LDPE Film	- Thick and highly conformable - Abrasion, solvent, and moisture resistant - Perforated spacing available
Acrylic Adhesive	- Solvent resistant - Excellent high and low temperature performance - Removes cleanly - will not leave residue on most surfaces*

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	5.5 mils	0.1397 mm	PSTC-133
Carrier Thickness	4.5 mils	0.1143 mm	PSTC-133
Adhesion to Steel	12 oz/in	1.31 N/cm	ASTM D-3330
Tensile Strength	12 lb/in	21.02 N/cm	ASTM D-3759
Elongation	500 %		
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	-40 to 190 °F	-40 to 88 °C	
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	24 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.