



Premium UL 181B-FX Listed Duct Tape-14 mils



Backing Carrier:	Printed Polyethylene Coated Cloth
Adhesive:	Rubber
Release Liner:	N/A
Standard Colors:	Metallic, Black, Silver
Specifications:	UL 181B-FX Listed
Standard Sizes:	48mm x 55M, 72mm x 55M

Applications

- A superior closure system for use on UL Listed flexible, non-metallic air duct
- Challenging bonding, protecting, bundling, and repair applications

Features

High strength PE Coated Cloth Backing

Aggressive Natural Rubber Adhesive

UL181B-FX Listed

Low VOC Content

Benefits

- Tough and durable
- Conformable to wrap ducts for an effective seal
- Excellent bond to sheet metal and other surfaces
- High strength to withstand vertical pull from the weight of the duct system
- Resistant to moisture and mold growth
- Meets code requirements and can contribute toward requirements for EA Credit 1 (Optimize Energy Performance) under LEED®
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	14 mils	0.356 mm	ASTM D-1000
Adhesion to Steel	45 oz/in	4.92 N/cm	PSTC-101
Adhesion to Backing	35 oz/in	3.83 N/cm	PSTC-101
Tensile Strength	29 lb/in	50.79 N/cm	ASTM D-1000
Flame Spread Index	15		ASTM E-84
Smoke Developed Index	15		ASTM E-84
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.