



Backing Carrier: LDPE Film
Adhesive AS/LS: Acrylic
Release Liner: Blue HDPE
Note: Clear, Transparent Orange

Applications

- Border and blockout tape for screenprinting - prevents ink from penetrating beyond the image area
- Bond directly to mesh for multi-color printing and pinhole covering

Features

LDPE Film

Acrylic Adhesive

HDPE Release Liner - Split Back

Benefits

- Superior conformability
- High stretch to maintain adhesion during frame re-tension
- Moisture and solvent resistant
- Good tack and moderate adhesion
- Clean removal from most surfaces
- Easy to apply
- Easy to apply & diecuttable

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	5.5 mils	0.1397 mm	PSTC-133
Carrier Thickness	4.5 mils	0.1143 mm	PSTC-133
Adhesion to Steel	25 oz/in	2.735 N/cm	ASTM D-3330
Tensile Strength	11 lb/in	19.26308 N/cm	ASTM D-3759
Elongation	5.5		
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	-40 to 190 °F	88 °C	
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 months from shipment date		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.