



Heavy-Duty Surface Protection Tape-Removable



- Backing Carrier:** LDPE Film
- Adhesive:** Acrylic (A200)
- Release Liner:** Self Wound or with 53# Clay Coated Kraft
- Standard Colors:** Clear
- Standard Sizes:** Incremental widths 1/4" - 48" x 180ft

Applications

- Protective masking on plastics and metals during shipping and assembly - saves money by reducing damage to delicate surfaces!
- Surface and label overlaminates

Features

LDPE Film

Acrylic Adhesive

Benefits

- Thick and tough
- Solvent, chemical, and moisture resistant
- Abrasion resistant
- Moderate tack - bonds to most surfaces
- Removes cleanly from most surfaces
- Easy to apply

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesion to Steel	10 oz/in	1.09 N/cm	ASTM D-3330
Tensile Strength	16 lb/in	28.02 N/cm	ASTM D-3759
Elongation	600 %		
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	-40 to 190 °F	-40 to 88 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.