



Foilastic Premium Butyl Window & Door Flashing-626



Backing Carrier: 2 mil Aluminum Foil - Printed
Adhesive: Butyl Rubber
Release Liner: White Kraft Paper
Standard Colors: Aluminum
Specifications: AMMA 711-13, ASTM E2112, 15 Year Limited Warranty
Note: 15 Year Limited Warranty
Standard Sizes: 4in x 100ft, 6in x 100ft, 6in x 50ft

Applications

- Window and door installations
- Sidewall sheathing seams
- Sealing other detail areas against water and air penetration
- Corner board abutments
- Deck-to-wall joints

Features

Benefits

2 mil Aluminum Foil Backing

- Conformable and durable
- Excellent air and moisture barrier properties
- Suitable for indefinite outdoor UV exposure

Premium Butyl Rubber Adhesive

- Provides permanent weather-tight seal on most clean, dry building surfaces
- Excellent all-temperature performance
- Compatible with sealants and caulking
- Self-healing after puncture

Kraft Paper Release Liner

- Easy to remove

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	17 mils	0.432 mm	ASTM D-1000
Adhesion to PVC	102 oz/in	11.21 N/cm	ASTM D330 Method F
Adhesion to Aluminum	99 oz/in	10.86 N/cm	ASTM D3330 Method F
Adhesion to Plywood	40 oz/in	4.38 N/cm	ASTM D330 Method F
Adhesion to OSB	35 oz/in	3.85 N/cm	ASTM D330 Method F
Tensile Strength	26 lb/in	45.53 N/cm	ASTM D3759
Installation Temperature	30 to 180 °F	-1 to 82 °C	
Operating Temperature	-30 to 200 °F	-34 to 93 °C	
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.