



Foilastic Premium Butyl Roof Flashing Tape

Backing Carrier:	2 mil Aluminum Foil
Adhesive:	Butyl Rubber
Release Liner:	LDPE Film
Standard Colors:	Aluminum
Specifications:	AAMA-711-22, ASTM E2112
Note:	Colors: Aluminum, Specifications: AAMA-711-22, ASTM E2112, 15 Year Limited Warranty, Standard Sizes: 48mm x 15M, 3in x 50ft, 4in x 50ft, 6in x 50ft, 9" x 50ft, 36" x 50ft, 12" x 50ft
Standard Sizes:	48mm x 15M, 3in x 50ft, 4in x 50ft, 6in x 50ft, 9" x 50ft, 36" x 50ft, 12" x 50ft

Applications

- Flashing hip, ridge, and penetration details on concrete tile roofs
- Deck-to-wall joints
- Sealing other detail areas against water and air penetration
- Sealing gutters, roof valleys and eaves, chimneys and vents, and rooftop duct systems
- Sheet metal repairs on mobile homes, trailers

Features

Benefits

2 mil Aluminum Foil Backing

- Conformable and durable
- Excellent air and moisture barrier properties
- Suitable for indefinite outdoor UV exposure

Premium Butyl Rubber Adhesive

- Provides permanent weather-tight seal on most clean, dry building surfaces
- Excellent all-temperature performance
- Compatible with sealants and caulking
- Self-healing after puncture
- Used properly, can contribute toward requirements for EA Credit 1 (Optimize Energy Performance) under LEED®

LDPE Liner

- Easy to use
- Moisture resistant



Foilastic Premium Butyl Roof Flashing Tape

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	35 mils	0.889 mm	ASTM D-1000
Adhesion to Backing	126 oz/in	13.83 N/cm	ASTM D3330 Method F
Adhesion to PVC	40 oz/in	4.38 N/cm	ASTM D3330 Method F
Adhesion to Aluminum	323 oz/in	35.38 N/cm	ASTM D3330 Method F
Adhesion to Plywood	138 oz/in	15.06 N/cm	ASTM D3330 Method F
Adhesion to OSB	115 oz/in	12.61 N/cm	ASTM D3330 Method F
Tensile Strength	24 lb/in	42.38 N/cm	ASTM D3759 Procedure A
Installation Temperature	30 to 180 °F	-1 to 82 °C	
Operating Temperature	-30 to 200 °F	-34 to 93 °C	
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

DRAFT

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.