



Seam & Seal Contractor Grade Sheathing Tape



Backing Carrier:	BOPP Film
Adhesive:	Acrylic
Release Liner:	N/A
Standard Colors:	Red, White, Clear
Standard Sizes:	48mm x 50M, 72mm x 50M

Applications

- Sealing and seaming joints and overlaps in housewrap and interior/exterior vapor barriers
- Sealing window and door flanges or frames
- Sealing exterior wall sheathing joints and extruded foam products
- Patching jobsite damage caused to wall sheathing and housewraps

Features

BOPP Backing

Acrylic Adhesive

Low VOC Content

Benefits

- Tough and durable
- Hand tearable for ease of use
- UV Resistant for outdoor installations up to 180 days
- Aggressive bond - won't flag or lift
- Mold and moisture resistant
- Performs well in cold temperatures as well as high heat and high humidity conditions
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	3.2 mils	0.081 mm	ASTM D-1000
Adhesion to Steel	50 oz/in	5.47 N/cm	PSTC-101
Tensile Strength	32 lb/in	56.04 N/cm	ASTM D-1000
Application Temperature	-5 to 180 °F	-20 to 82 °C	
Operating Temperature	-40 to 212 °F	-40 to 100 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	24 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.