



Shadowlastic Extreme Cold Weather Window & Door Flashing Tape

| Features                   | Benefits                                                                                                                                                                                                                                                                                                                                                                     |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Woven Polyethylene Backing | <ul style="list-style-type: none"><li>Conformable and durable</li><li>Excellent air and moisture barrier properties</li><li>Suitable for up to 1 year outdoor UV exposure (Note: Black is longer resistance than white)</li></ul>                                                                                                                                            |
| Butyl Rubber Adhesive      | <ul style="list-style-type: none"><li>Provides permanent weather-tight seal on most clean, dry building surfaces</li><li>Excellent cold temperature adhesion</li><li>Compatible with sealants and caulking</li><li>Self-healing after puncture</li><li>Used properly, can contribute toward requirements for EA Credit 1 (Optimize Energy Performance) under LEED®</li></ul> |
| PET Film Release Liner     | <ul style="list-style-type: none"><li>Easy to remove</li></ul>                                                                                                                                                                                                                                                                                                               |

DRAFT

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.