



## Clear Butyl Window & Door Flashing Tape

|                         |                                                           |
|-------------------------|-----------------------------------------------------------|
| <b>Backing Carrier:</b> | Woven Polyethylene (Unprinted or Printed)                 |
| <b>Adhesive:</b>        | Clear Butyl Rubber                                        |
| <b>Release Liner:</b>   | PET Film                                                  |
| <b>Standard Colors:</b> | Gray, White                                               |
| <b>Specifications:</b>  | Listed on AAMA's Verified Components List for AAMA 711-22 |
| <b>Note:</b>            | Listed on AAMA's Verified Components List for AAMA 711-20 |
| <b>Standard Sizes:</b>  | 4" x 75Ft, 6" x 75Ft, 9" x 75Ft, 12" x 75ft               |

### Applications

- Window and door installations
- Side-wall sheathing seams
- Sealing other detail areas against water and air penetration
- Corner board abutments
- Deck-to-wall joints

| Features                           | Benefits                                                                                                                                                                                                                                                                                                                                                                                     |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Woven Polyethylene Backing</b>  | <ul style="list-style-type: none"> <li>• Conformable and durable</li> <li>• Excellent air and moisture barrier properties</li> <li>• Suitable for up to 1 year outdoor UV exposure</li> </ul>                                                                                                                                                                                                |
| <b>Clear Butyl Rubber Adhesive</b> | <ul style="list-style-type: none"> <li>• Provides permanent weather-tight seal on most clean, dry building surfaces</li> <li>• Excellent cold temperature adhesion</li> <li>• Compatible with sealants and caulking</li> <li>• Self-healing after puncture</li> <li>• Used properly, can contribute toward requirements for EA Credit 1 (Optimize Energy Performance) under LEED®</li> </ul> |
| <b>PET Film Liner</b>              | <ul style="list-style-type: none"> <li>• Easy to remove</li> </ul>                                                                                                                                                                                                                                                                                                                           |



## Clear Butyl Window & Door Flashing Tape

### Typical Test Values

|                                             | Standard UOM  | Metric UOM      | Test Method            |
|---------------------------------------------|---------------|-----------------|------------------------|
| <b>Total Thickness (without Liner)</b>      | 14.5 mils     | 0.37 mm         | ASTM D-1000            |
| <b>Adhesion to Backing</b>                  | 104 oz/in     | 11.38 N/cm      | ASTM D3330 Method F    |
| <b>Adhesion to Vinyl</b>                    | 115 oz/in     | 12.58 N/cm      | ASTM D3330 Method F    |
| <b>Adhesion to Aluminum</b>                 | 122 oz/in     | 13.35 N/cm      | ASTM D3330 Method F    |
| <b>Adhesion to Plywood</b>                  | 107 oz/in     | 11.71 N/cm      | ASTM D3330 Method F    |
| <b>Adhesion to OSB</b>                      | 96 oz/in      | 10.5 N/cm       | ASTM D3330 Method F    |
| <b>Tensile Strength (Machine Direction)</b> | 2855 PSI      |                 | ASTM D 1970 Sec 7.3    |
| <b>Tensile Strength</b>                     | 52 lb/in      |                 | ASTM D3759 Procedure A |
| <b>Elongation</b>                           | 36 %          |                 | ASTM D3759 Procedure A |
| <b>Installation Temperature</b>             | 176 °F        | -23 to 80 °C    |                        |
| <b>Operating Temperature</b>                | -30 to 200 °F | -34 to 93 °C    |                        |
| <b>Recommended Storage Temperature</b>      | 60 to 80 °F   | 15.6 to 26.7 °C |                        |
| <b>Recommended Storage Humidity</b>         | 40 to 60 %    |                 |                        |
| <b>Shelf Life (Standard)</b>                | 36 Months     |                 |                        |

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.