



Stucco Masking Tape



Backing Carrier:	PE Coated Cloth
Adhesive:	Rubber
Release Liner:	N/A
Standard Colors:	Red
Specifications:	Tested in accordance with UL 723
Standard Sizes:	48mm x 55m

Applications

- Outdoor masking on wood, metal and concrete
- Home and general repair
- Hanging PE sheeting for outdoor stucco installations
- Bundling, patching, and mending

Features

PE-Coated Cloth Backing

Natural rubber based adhesive

Low VOC Content

Benefits

- Excellent balance of tensile strength and tearability
- Aggressive adhesion to rough surfaces
- Superior holding power for hanging applications
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	10 mils	0.254 mm	ASTM D-1000
Adhesion to Steel	50 oz/in	5.47 N/cm	PSTC-101
Rolling Ball Tack	2.5" inches		
Tensile Strength	22 lb/in	38.53 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		