



Multi-Purpose Filament Tape



- Backing Carrier:** Fiberglass-Reinforced Polypropylene Film
- Adhesive:** Synthetic Rubber
- Release Liner:** N/A
- Standard Colors:** Transparent
- Standard Sizes:** 12mm x 55M, 18mm x 55M, 24mm x 55M

Applications

- General purpose strapping tape for light-duty applications
- Package and box sealing
- Pallet and corrugate strapping
- Bundling and wrapping

Features

- Mono-Directional Filament Reinforcement
- Rubber Adhesive

Benefits

- High strength
- Durable
- Provides a strong long-term bond
- No flagging or lifting

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	4.5 mils	0.114 mm	ASTM D-1000
Adhesion to Steel	90 oz/in	9.85 N/cm	PSTC-101
Tensile Strength	110 lb/in	192.64 N/cm	ASTM D-1000
Elongation	6 %		
Operating Temperature	-22 to 130 °F	-30 to 55 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	24 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.