



PVC Utility Pipewrap Tape

- Backing Carrier:** Printed PVC Film
- Adhesive:** Rubber Based
- Release Liner:** N/A
- Standard Colors:** Black
- Specifications:** Meets UPC, ANSI & IAPMO standards
- Standard Sizes:** 48mm x 31M

Applications

- Under and above-ground pipe wrap applications
- Industrial assembly
- Protecting metal pipes and parts against mechanical and chemical wear

Features	Benefits
PVC Film Backing	• Tough and conformable • Protects against UV, moisture, acids, alkalizes, abrasion, and corrosion
Rubber Adhesive	• Provides a strong long-term bond • No flagging or lifting

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	10 mils	0.254 mm	ASTM D-1000
Adhesion to Steel	15 oz/in	1.64 N/cm	PSTC-101
Tensile Strength	20 lb/in	35.03 N/cm	ASTM D-1000
Elongation	100%		
Operating Temperature	200 °F	-18 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.