



Double-Coated Acrylic Splicing Tape



- Backing Carrier: Polyester Film
- Adhesive: Acrylic
- Release Liner: White Kraft paper
- Standard Colors: Red (Adhesive Color)
- Standard Sizes: 1" x 60Yd, 2" x 60Yd

Applications

- Corrugate splicing/manufacturing
- Laminating & frame mounting
- Printing and plate mounting applications
- Paper converting
- Foil manufacturing
- High temperature laminating

FeaturesBenefits

- | | |
|---------------------------------|---|
| Polyester Film Reinforcement | <ul style="list-style-type: none">Outstanding conformability for continuous adhesion on irregular surfacesConformable and moisture resistantThin for low-profile splices |
| Acrylic Adhesive | <ul style="list-style-type: none">Good tack and adhesionEliminates downtime from adhesive bleeding and splice failureRed for visible splicesExcellent temperature resistance |
| White Kraft Paper Release Liner | <ul style="list-style-type: none">Die-cutable |

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	3.8 mils	0.097 mm	ASTM D-1000
Adhesion to Steel	25 oz/in	2.74 N/cm	PSTC-101
Tensile Strength	6 lb/in	10.51 N/cm	ASTM D-1000
Elongation	30%		ASTM D-1000
Operating Temperature	395 °F	-17 to 201 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	24 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.