



General Purpose PE Film Tape



Backing Carrier: Polyethylene Film
Adhesive: Rubber
Release Liner: N/A
Standard Colors: Orange, Black
Standard Sizes: 48mm x 55m, 72mm x 55m

Applications

- Stucco and plaster masking
- Bunding, wrapping, and repairs
- General purpose outdoor masking
- General purpose abatement applications such as hanging and patching PE sheeting, securing waste disposal bags, and more

Features

Polyethylene Film Backing

Natural Rubber Based Adhesive

Benefits

- Conformable and flexible
- Excellent durability and solvent resistance
- Withstands outdoor exposure and moisture
- High tack for a secure bond
- Repositionable and clean removal - no residue

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	7.5 mils	0.191 mm	ASTM D-1000
Adhesion to Steel	50 oz/in	5.47 N/cm	PSTC-101
Adhesion to Backing	25 oz/in	2.74 N/cm	PSTC-101
Tensile Strength	25 lb/in	43.78 N/cm	ASTM D-1000
Elongation	70 %		
Operating Temperature	40 to 180 °F	4 to 82 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	24 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.