



UV-Resistant Multi-Purpose PE Film Tape

Backing Carrier: Polyethylene Film
Adhesive: Synthetic Rubber
Note: Red available for non-Marine applications

Applications

- Boat wrap industry and other equipment storage and protection uses requiring shrink wrap and heat shrink tape
- Bundling, wrapping and repairs
- Heavy-duty polyethylene splicing and hanging
- Short-term masking for stucco and plaster
- Short-term (up to 28 days) outdoor storage uses
- Surface protection

Features

Benefits

Polyethylene Film Backing

- Short-term UV resistance for outdoor uses up to 28 days
- Conformable and flexible
- Excellent durability and solvent resistance
- Low elongation for consistent surface bond

Synthetic Rubber Adhesive

- High tack for good quick stick
- Excellent shear strength
- Repositionable and clean removal from many surfaces

Low VOC, Contains no heavy metals

- Environmentally friendly and safe to use

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness (Colors)	7 mils	0.1778 mm	
Adhesion to Steel	66 oz/in	7.2204 N/cm	
Adhesion to Backing	32 oz/in	3.5008 N/cm	
Tensile Strength	20 lb/in	35.0256 N/cm	
Elongation	0.68		
Application Temperature	30 to 160 °F	-1 to 71 °C	
Operating Temperature	20 to 200 °F	-7 to 93 °C	
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	24 months from date of manufacture		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.