



Multi-Purpose PE Film Tape



Backing Carrier:	Polyethylene Film
Adhesive:	Synthetic Rubber
Release Liner:	N/A
Standard Colors:	Red, White, Black, Silver, Teal, Blue, Orange, Clear, Pink*, Green*
Specifications:	Meets NFPA-701, Tested in Accordance to ASTM E84
Standard Sizes:	48mm, 72mm, 96mm x 55M

Applications

- Abatement industry: hang and patch poly sheeting, seal waste disposal bags, etc.
- Short-term masking for stucco and plaster
- Temporary surface protection
- Labeling and color coding
- Bundling, wrapping, and repairs
- Convention industry - bundling carpet, securing poly carpet protection, color coding, etc.

Features

Polyethylene Film Backing

Synthetic Rubber Adhesive

Low VOC, Contains no heavy metals (such as lead and chromium)

Benefits

- Conformable and flexible
- Excellent durability and solvent resistance
- Low elongation for consistent surface bond
- Pinked Edge available for hand tearability
- High tack for good quick stick
- Excellent shear strength
- Repositionable and clean removal from many surfaces
- Environmentally friendly & safe to use.

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	7 mils	0.178 mm	ASTM D-1000
Adhesion to Steel	70 oz/in	7.66 N/cm	PSTC-101
Adhesion to Backing	30 oz/in	3.28 N/cm	PSTC-101
Tensile Strength	20 lb/in	35.03 N/cm	ASTM D-1000
Elongation	85 %		
Permeance	0.11 US Perms		ASTM F1249
Smoke Developed Index	30		
Application Temperature	30 to 160 °F	-1 to 71 °C	
Operating Temperature	20 to 200 °F	-7 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	24 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.