



7 mil General Purpose PVC Electrical Tape



- Backing Carrier: PVC Film
- Adhesive: Rubber
- Release Liner: N/A
- Standard Colors: Black
- Specifications: UL 510 Classified
- Standard Sizes: 3/4" x 60Ft

Applications

- Wire splicing
- Wire insulation
- Spiral wrapping electrical wire and harnesses

Features

Benefits

- | | |
|--------------------------|---|
| PVC Backing | <ul style="list-style-type: none">Stretchy and conformable for wrapping wiresDurableConformable |
| Rubber Adhesive | <ul style="list-style-type: none">Provides a strong long-term bondNo flagging or lifting |
| UL 510 Classified | <ul style="list-style-type: none">Meets requirements for most electrical applications |

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	7 mils	0.178 mm	ASTM D-1000
Adhesion to Steel	20 oz/in	2.19 N/cm	PSTC-101
Tensile Strength	18 lb/in	31.52 N/cm	ASTM D-1000
Elongation	200 %		
Dielectric Strength	600 V		
Operating Temperature	40 to 180 °F	4 to 82 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.