



- Backing Carrier:** Polyethylene Film
- Adhesive:** Rubber
- Release Liner:** N/A
- Standard Colors:** Red
- Standard Sizes:** 48mm x 55m, 72mm x 55m

Applications

- Used to block screens from moisture and chemicals during screen printing
- General purpose industrial bundling, patching, wrapping, and repairing

Features

Polyethylene Film Backing

Natural rubber based adhesive

Benefits

- Conformable and flexible
- Excellent durability and solvent resistance
- Red for high visibility
- High tack for a secure bond
- Repositionable and clean removal - no residue

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	8 mils	0.203 mm	ASTM D-1000
Adhesion to Steel	60 oz/in	6.56 N/cm	PSTC-101
Tensile Strength	21 lb/in	36.78 N/cm	ASTM D-1000
Elongation	70 %		
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	24 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.