



1.6 mil Utility Carton Sealing Tape



|                  |                                                   |
|------------------|---------------------------------------------------|
| Backing Carrier: | Polypropylene Film                                |
| Adhesive:        | Synthetic Rubber                                  |
| Release Liner:   | N/A                                               |
| Standard Colors: | Transparent                                       |
| Specifications:  | Meets CFR21.B.175.105 for indirect food packaging |
| Standard Sizes:  | 48mm x 50M, 48mm x 100M                           |

Applications

- Sealing light-weight packages
- Bundling and wrapping

| Features | Benefits |
|----------|----------|
|----------|----------|

|                   |                                                                                                                                                                        |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BOPP Film Backing | <ul style="list-style-type: none"><li>Strong and durable</li><li>Abrasion resistant</li></ul>                                                                          |
| Rubber Adhesive   | <ul style="list-style-type: none"><li>High tack for a secure bond to most corrugate</li><li>No flagging or lifting</li><li>Moisture &amp; chemical resistant</li></ul> |

Typical Test Values

|                                 | Standard UOM | Metric UOM | Test Method |
|---------------------------------|--------------|------------|-------------|
| Total Thickness                 | 1.6 mils     | 0.041 mm   | ASTM D-1000 |
| Adhesion to Steel               | 44 oz/in     | 4.81 N/cm  | PSTC-101    |
| Tensile Strength                | 22 lb/in     | 38.53 N/cm | ASTM D-1000 |
| Elongation                      | 165 %        |            |             |
| Operating Temperature           | 120 °F       | 48 °C      |             |
| Recommended Storage Temperature | 60 to 80 °F  |            |             |
| Recommended Storage Humidity    | 40 to 60 %   |            |             |
| Shelf Life (Standard)           | 24 Months    |            |             |

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.