



Automotive Surface Protection Tape



Backing Carrier: Exterior-Grade Aliphatic Polyurethane

Adhesive: Acrylic (A106)

Release Liner: 94# Coated Kraft Paper

Standard Colors: Transparent

Standard Sizes: Incremental sizes 1/4" - 48" x 108Ft

Applications

- Surface protection on high-wear surfaces prone to scratching, chipping, and weathering
- Surface protection for air foil and ground effects panels on racing cars and trucks
- Automotive stoneguard protection.

Features

Polyurethane Film Backing

Acrylic Adhesive

Kraft Paper Release Liner

Benefits

- Non-yellowing for long term applications
- Abrasion & UV resistant
- Printable & Paintable
- Conformable for curves and irregular surfaces
- Transparent for easy inspection
- High strength bond to smooth or irregular surfaces
- Will not dry out, lift, or stain
- Smooth clean release - easy to use
- Die cuttable

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	14.5 mils	0.368 mm	PSTC-133
Adhesion to Steel	110 oz/in	12.03 N/cm	ASTM D-3330
Tensile Strength	80 lb/in	140.1 N/cm	ASTM D-3759
Elongation	500 %		
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	-40 to 275 °F	-40 to 135 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.