



Polyurethane Surface Protection Tape



Backing Carrier: Interior-Grade Aromatic Polyurethane

Adhesive: Acrylic (A106)

Release Liner: 94# Coated Kraft Paper

Standard Colors: Matte Black

Standard Sizes: Incremental sizes 1/4" - 31" x 108Ft

Applications

- Surface protection on high-wear surfaces prone to scratching, chipping, and weathering
- Moisture barrier applications
- Insulation and sound damping
- Squeak and rattle protection
- Indoor industrial surface protection

Features

Polyurethane Film Backing

Acrylic Adhesive

Kraft Paper Release Liner

Benefits

- Protects and holds under heavy usage
- Tough and durable - abrasion resistant
- Conformable for curves and irregular surfaces
- High strength bond to smooth or irregular surfaces
- Excellent aging characteristics
- Smooth clean release - easy to use
- Die cuttable

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Adhesion to Steel	75 oz/in	8.21 N/cm	ASTM D-3330
Tensile Strength	40 lb/in	70.05 N/cm	ASTM D-3759
Elongation	700 %		
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	-40 to 250 °F	-40 to 121 °C	
Recommended Storage Temperature	60 to 80 °F		
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	12 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.