



Stucco Masking Duct Tape



Backing Carrier: PE Coated Cloth
Adhesive: Rubber
Release Liner: N/A
Standard Colors: Red, White, Silver
Note: Colors: Red, White, Silver
Standard Sizes: 48mm x 55m

Applications

- Masking of construction materials such as vinyl, wood, aluminum, and anodized metals
- Bundling, patching, and mending
- Protecting windows and doors during stucco applications
- Long-term outdoor repairs

Features

PE-Coated Cloth Backing

Natural Rubber Adhesive

Low VOC Content

Benefits

- Excellent UV resistance for long-term outdoor applications
- Clean, crisp, straight tear
- Aggressive adhesion to rough surfaces
- Clean removal, no residue for at least 30 days
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	9 mils	0.23 mm	ASTM D-1000
Adhesion to Steel	80 oz/in	8.75 N/cm	PSTC-101
Tensile Strength	30 lb/in	54.5 N/cm	ASTM D-1000
Elongation	0.2		
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		