



Heavy-Duty Permanent PE Film Tape

Backing Carrier: PE (Polyethylene) Film



| Features                                                      | Benefits                                                                                                                                                                                                                                                                                       |
|---------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Polyethylene Film Backing                                     | <ul style="list-style-type: none"><li>Conformable and flexible</li><li>Excellent durability and solvent resistance</li><li>Low elongation for consistent surface bond</li><li>Low permeability for vapor barrier sealing</li><li>Pinked/Serrated Edge available for hand tearability</li></ul> |
| Synthetic Rubber Adhesive                                     | <ul style="list-style-type: none"><li>Permanent, long-term bond</li><li>Aggressive, high tack formulation for instant bond</li><li>Excellent shear strength</li><li>Maintains adhesive integrity for up to 12 days of outdoor exposure</li></ul>                                               |
| Low VOC, Contains no heavy metals (such as lead and chromium) | <ul style="list-style-type: none"><li>Environmentally friendly and safe to use</li></ul>                                                                                                                                                                                                       |

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.