



7 mil General Purpose Electrical Tape-Colors



Backing Carrier: PVC Film

Adhesive: Rubber

Standard Colors: Blue, Green, Red, White, Yellow

Specifications: UL

Applications

- Wire splicing
- Wire insulation
- Spiral wrapping electrical wire and harnesses
- Color coding

Features

Benefits

PVC Backing

- Stretchy and conformable for wrapping wires
- Durable
- Conformable

Rubber Adhesive

- Provides a strong long-term bond
- No flagging or lifting

UL 510 Classified

- Meets requirements for most electrical applications

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	7 mils	0.1778 mm	ASTM D-1000
Adhesion to Steel	25 oz/in	2.735 N/cm	PSTC-101
Tensile Strength	20 lb/in	35.0256 N/cm	ASTM D-1000
Elongation	2		
Dielectric Strength	9500 V		
Operating Temperature	40 to 180 °F	4 to 82 °C	
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	5 years from date of manufacture		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.