



Double-Sided Abatement Tape



Backing Carrier: Cloth/Paper Lamination
Adhesive AS/LS: Differential Rubber
Release Liner: Blue LDPE
Standard Colors: Natural/Blue
Note: Colors: Natural/Blue
Standard Sizes: 48mm x 20Yd

Applications

- Securing tarps or poly sheeting materials to surfaces such as wood, glass, aluminum, plastics, and vinyl
- Holds materials in place without damaging surfaces for painting, cleaning, sanding, construction, or abatement applications

Features

Benefits

Cloth reinforcement

- Hand-tearable and durable like duct tape
- Conformable and moisture resistant

Differential Adhesive

- Provides aggressive bond to tarps and sheeting
- Blue side removes clean from surfaces for up to 14 days
- High strength to hang heavy sheeting materials

Release Liner

- Easy to remove, easy to use

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	15 mils	0.381 mm	ASTM D-1000
Adhesion to Steel (Air Side)	25 oz/in	2.74 N/cm	PSTC-101
Adhesion to Steel (Liner Side)	40 oz/in	4.38 N/cm	PSTC-101
Static Shear (1" x 1" x 1 kg)	10000 Hours		
Static Shear Air Side (1" x 1" x 1 kg)	10000 Hours		
Tensile Strength	63 lb/in	110.33 N/cm	ASTM D-1000
Elongation	0.11		
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	24 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.