



UL181B-FX Listed Film Tape



Backing Carrier: Printed Biaxially-Oriented Polypropylene Film

Adhesive: Acrylic

Specifications: UL

Note: UL 181B-FX Listed

Applications

- Designed and sized for sealing dryer vent exhaust ducts and connections to increase system performance.
- Seals bubble and reflective insulation materials
- Tough, contractor-grade closure system intended for use on UL Listed flexible, non-metallic ducts.

Features

UL 181B-FX Listed

Acrylic Adhesive

Biaxially-Oriented Polypropylene Film

Benefits

- Meets code requirements for sealing flexible air ducts and connections.
- Can contribute toward satisfying EA Credit 1 (Optimize Energy Performance) under LEED®.
- Excellent, long-lasting adhesion.
- Low-odor adhesive.
- Mold and moisture-resistant.
- Tough and durable.

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	3.1 mils	79 μm	
Adhesion to Steel	45 oz/in	4.92 N/cm	
Tensile Strength	34 lb/in	59.54 N/cm	
Installation Temperature	-10 to 180 °F	-17 to 82 °C	
Operating Temperature	-40 to 212 °F	100 °C	
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	24 months from date of manufacture		