




Insulation Seaming Tape



Backing Carrier:	Foil/Scrim/Kraft Paper Laminate
Adhesive:	Synthetic Rubber
Release Liner:	Unbleached Natural Kraft Paper
Standard Colors:	Aluminum
Specifications:	Tested in accordance with UL723
Standard Sizes:	72mm x 46M

Applications

- Vapor barrier seal for insulation facing
- Sealing insulation and repairing in cooler/refrigeration applications

Features

Foil/Scrim/Kraft Laminate Backing

Synthetic Rubber Adhesive

Low VOC Content

Benefits

- High strength and tear resistant
- UV, moisture, and mold resistant
- Non-solvent for less odor and low VOC content
- Super high tack, aggressive bond to surfaces
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	9.25 mils	0.235 mm	ASTM D-1000
Adhesion to Steel	70 oz/in	7.66 N/cm	PSTC-101
Tensile Strength	35 lb/in	61.29 N/cm	ASTM D-1000
WVTR	>0.02 perms		Mocon (100° F, 90% RH)
Flame Spread Index	15		
Smoke Developed Index	15		
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.