



UVSix 11.5 Mil Clean Removal Duct Tape

Backing Carrier: PE Coated Cloth
Adhesive: Rubber
Release Liner: N/A
Standard Colors: Slate Blue, Red
Note: Colors: Slate Blue, Red
Standard Sizes: 48mm x 55m, 72mm x 55m

Applications

- Multiple uses in power plants and on ships.
- Color coding
- Holding dosimeters, securing clothing and gloves, wrapping pipe ends, insulation & duct sealing
- Heavy-duty packaging and bundling
- Media-blast protection
- Wrapping pipe ends, insulation & duct sealing

Features

PE-Coated Cloth Backing

Natural Rubber-Based Adhesive

Benefits

- High tensile strength for difficult applications
- Abrasion and puncture resistant
- Crisp, straight tear
- UV resistant for 6 months
- Aggressive adhesion - including adhesion to extremely rough materials
- Clean removal with little or no residue for up to 6 months from most surfaces

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	11.5 mils	0.29 mm	ASTM D-1000
Adhesion to Steel	80 oz/in	8.85 N/cm	PSTC-101
Adhesion to Backing	45 oz/in	5 N/cm	PSTC-101
Tensile Strength	26 lb/in	46 N/cm	ASTM D-1000
Flame Spread Index	15		ASTM E84
Smoke Developed Index	30		ASTM E84
Operating Temperature	40 to 200 °F	4 to 93 °C	
Recommended Storage Temperature	60 to 80 °F	15.6 to 26.7 °C	
Recommended Storage Humidity	40 to 60 %		
Shelf Life (Standard)	36 Months		

Values shown are based on laboratory testing and represent typical product characteristics. Actual performance will vary depending on application conditions, and no guarantee of performance is made. The user is responsible for determining suitability for the intended application. No express or implied warranty, including merchantability or fitness for a particular purpose, is made.